



Model: _____ Item #: _____ Date: _____

Project: _____ Qty: _____ Approved By: _____

Gas Connector Hose Only

Gas Connectors



Standard Features

- For use with stationary and caster-mounted commercial kitchen equipment
- Male NPT End fittings rotate 360°
- Heavy duty stainless steel corrugated tubing for flexibility
- Heavy duty stainless steel radial wrap prevents hose from stretching
- PVC Protective coating with anti-microbial agent for easy cleaning
- Welded construction for added durability
- For Indoor Use Only

Specifications

| | |
|---------------------|-------------------------------|
| Pressure | ▪ 1/2 psi |
| End Fittings | ▪ Carbon Steel, Chrome Plated |
| Tubing | ▪ Stainless Steel 304 |
| Braiding | ▪ Stainless Steel 304 |

Includes:

| No. | Name | Description |
|-----|---------------|--|
| 1 | Gas Connector | For stationary and caster-mounted kitchen equipment. |

Visit krowne.com for complete replacement parts.

Product Compliance

- ANSI Z21.41-2014 • CSA 6.9-2014 Quick Disconnect Devices For Use With Gas Fuel Appliances
- ANSI Z21.69-2009 • CSA 6.16-2009 Connectors For Moveable Gas Appliances
- ANSI Z21.69a-2012 • CSA 6.16a-2012 Addenda

| Model No. | Interior Size | Length | BTU/hr |
|-----------|---------------|--------|--------|
| M5024 | 1/2" | 24" | 87K |
| M5036 | 1/2" | 36" | 77K |
| M5048 | 1/2" | 48" | 68K |
| M5060 | 1/2" | 60" | 60K |
| M5072 | 1/2" | 72" | 55K |
| M7524 | 3/4" | 24" | 232K |
| M7536 | 3/4" | 36" | 218K |
| M7548 | 3/4" | 48" | 180K |
| M7560 | 3/4" | 60" | 158K |
| M7572 | 3/4" | 72" | 139K |
| M10024 | 1" | 24" | 414K |
| M10036 | 1" | 36" | 379K |
| M10048 | 1" | 48" | 334K |
| M10060 | 1" | 60" | 294K |
| M10072 | 1" | 72" | 279K |
| M12524 | 1-1/4" | 24" | 699K |
| M12536 | 1-1/4" | 36" | 615K |
| M12548 | 1-1/4" | 48" | 541K |
| M12560 | 1-1/4" | 60" | 476K |
| M12572 | 1-1/4" | 72" | 419K |

WARNING: Restraining Kits are required by law for all moveable gas equipment
California Proposition 65 Warning

