



OUTDOOR Mobile Fryer

CS-ODF Series



Model
CS-ODF-2



Standard Features & Benefits

CONSTRUCTION: Cabinet-frame is constructed of 304SS for durability and easy cleaning. Stainless steel fry tank. (2) Two locking casters combined with (2) two 13 wheels for easy transport across rough terrain.


CONTROLS: Thermostat - 200°F to 400°F, automatic standing pilot with 100% safety shut off and built in pressure regulator, high limit control for back-up safety, reliable brass burner valves. Optimal pressures are 4" WC for natural gas and 10" WC for propane. Manifold size is 3/4" NPT. All controls are tested and confirmed in good working order.

BURNERS: Cast iron burners each rated at 31,000BTU's. Model CS-ODF-1 has (3) burners and model CS-ODF-2 has (6) burners.

TANK: Easy cleaning, corrosion resistant stainless steel tube type tank for maximum surface heat transfer. Built in flue deflector. Deep cold zone allows food particles to sink below tubes reducing shortening breakdown and taste transfer as well as extending the life and quality of fryer shortening. Large diameter ball valve for quick draining. 304 Stainless tank cover included to reduce air and dust exposure to oil overnight (*not for holding oil in tank during transport*).

BASKETS: Two heavy duty, nickel plated wire baskets with coated handles. Easy cleaning removeable hangers firmly suspends loaded baskets out of frying vat.

SPECIFICATIONS			
Model		CS - ODF-1	CS - ODF-1
Width	in.	30	46.5
	mm	762	1181
Depth	in.	31.5	31.5
	mm	800	800
Height to flue top	in.	50	50
	mm	1270	1270
Height to cook top	in.	37.5	37.5
	mm	953	953
Approx. Ship Weight	lbs.	264	400
	kgs.	120	158
Total BTU		93,000	186,000

 **WARNING:** This product can expose you to certain chemicals, which are known to the State of California to cause cancer or birth defects or other reproductive harm. For more information go to: www.P65Warnings.com

NOTICE: In an ongoing effort of product development & improvement, Comstock-Castle reserves the right to change specifications and product design without notice. Such modifications do not entitle the buyer to corresponding changes or replacements for previously purchased equipment.




Comstock-Castle Stove Co. • 119 W. Washington St. • Quincy, IL. 62301
Tel.: 217-223-5070 • Fax.: 217-223-0007 • Web: www.castlestove.com





CS-ODF Series Specs



Mechanical Specs

Model Number	Total BTU	# of Baskets	# of Burners	Overall Dim W. x H. x D.	Carton Dim W. x H. x D.	Shipping Weight
CS-ODF-1	93,000	2	3	38" x 50" x 32"	38" x 50" x 32"	275 lbs.
CS-ODF-2	186,000	4	6	55" x 50" x 32"	55" x 50" x 32"	420 lbs.



WARNING: This product can expose you to certain chemicals, which are known to the State of California to cause cancer or birth defects or other reproductive harm. For more information go to: www.P65Warnings.com

NOTICE: In an ongoing effort of product development & improvement, Comstock-Castle reserves the right to change specifications and product design without notice. Such modifications do not entitle the buyer to corresponding changes or replacements for previously purchased equipment.



Comstock-Castle Stove Co. • 119 W. Washington St. • Quincy, IL. 62301
Tel.: 217-223-5070 • Fax.: 217-223-0007 • Web: www.castlestove.com

