

|          |           |
|----------|-----------|
| Project: | Quantity: |
| Model #: | Approval: |

For Commercial Use Only

### XS500YX 58" Curved Glass Top Display Ice Cream Freezer - 17.7 Cu. Ft.

#### FEATURES

- Curved glass top lid with two sliding doors
- White painted steel with gray plastic trim exterior
- Steel interior walls
- Includes low profile casters with brakes
- LED interior lighting
- Built-in lock for security
- Holds temperature between -14.8°F to -0.4°F
- Rear drain plug for manual defrosting
- Coated wire basket included
- Hydro-Carbon R290 refrigerant

This Coldline curved glass top ice cream display freezer is designed to boost your impulse sales of ice cream, popsicles, pints of sorbet, and frozen appetizers. It features a high-efficiency refrigeration system, a durable stainless steel design, and a high-accessibility curved glass top display. Built for school concession stands, diners, and convenience stores, this ice cream display machine keeps top-selling frozen novelties within easy reach to boost selling potential.

- cETLus Listed
  - ETL Sanitation Listed
- Certified to NSF Standard



USR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.

## TECHNICAL DATA

### DIMENSIONS

|                      |                          |
|----------------------|--------------------------|
| Exterior Dimensions  | 58.1"L x 29.8"D x 33.1"H |
| Packaging Dimensions | 61"L x 32"D x 39"H       |
| Net Volume           | 17.7 cu. ft.             |
| Unit Weight          | 176 lb.                  |
| Shipping Weight      | 209 lb.                  |

### ELECTRICAL

|                   |            |
|-------------------|------------|
| Voltage           | 115        |
| Hertz             | 60         |
| Phase             | 1          |
| Kilowatts         | 0.33       |
| Plug Type         | NEMA 5-15P |
| Power Cord Length | 72"        |

### COOLING

|                        |                   |
|------------------------|-------------------|
| Temperature Range      | -14.8°F to -0.4°F |
| Refrigerant            | R290              |
| Max. Ambient Tem       | 90°F              |
| Defrosting             | Manual            |
| Temperature Controller | Manual            |

### CONSTRUCTION

|                         |                                   |
|-------------------------|-----------------------------------|
| Exterior Material       | Painted Steel                     |
| Interior Material       | Steel                             |
| Insulation Material     | Foamed-in-Place Polyurethane      |
| Top Style               | Curve                             |
| Door Panel              | LOW-E + Tempered                  |
| Door Type               | Sliding                           |
| Lock                    | Yes                               |
| Door Frame Color        | Gray                              |
| Basket                  | (5) 21.8"L x 9.96"D x 12.85"H     |
| Basket Material         | Coated Wire                       |
| Drain Plug              | Rear                              |
| Interior Light          | LED                               |
| Mobility Wheels/Casters | (4) Qty: 2 with brakes, 2 without |

## TECHNICAL DRAWING

MODEL: XS500YX

MFR ITEM #: XS-500YX



NEMA 5-15P

