

SC-OD35E-33L-B-LED - MOBILE MERCHANDISER



SC-OD35E-33L-B-LED

MODEL NO.	DESCRIPTION	LENGTH	DEPTH	HEIGHT	VOLTAGE	AMPS	HP	POWER CORD	EST. SHIP WEIGHT
SC-OD35E-33L-B-LED	Self Contained	33.75"	34.5"	60"	115	14.0	1/2	5-20P	700

(ALL WHITE OR ALL BLACK, NO EXTRA CHARGE—IF COLORS ARE MIXED AN ADDITIONAL CHARGE WILL APPLY)

Prefix	Suffix
SC = Self Contained	B = Black
R = Remote	W = White
	S = Stainless Steel
	LED = LED lighting

- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
- Cases are equipped with drains; check your local building codes for connection requirements.
- Specification subject to change without notice



Howard McCray • 831 East Cayuga St • Philadelphia, PA 19124 USA • (215) 464-6800
 1-800-344-8222 • Fax (215) 969-4890 • E-Mail: sales@howardmccray.com • www.howardmccray.com

STANDARD SPECIFICATIONS AND OPTIONAL FEATURES

CONSTRUCTION

- UL Classified to ANSI/NSF 7
- Foamed in place CFC free foam
- Heavy gauge steel super structure

INTERIOR

- Black end panels
- Removable black floor pans
- Black perforated rear wall (for even air distribution)
- Full length lighting at top of unit

EXTERIOR

- Black ends and front
- Removeable front grill allows for cleaning and servicing

FINISHES

- Black end panels
- Black front rail
- Black end trim

LIGHTING

- 2 strips of LED lighting inside top of unit

ELECTRICAL REQUIREMENTS

- Cord and Plug
- Receptacle on back (separate circuit)

REFRIGERATION

- Low velocity fans located below deck area (to insure even flow of air)
- Electronic Control System with automatic air defrost to maintain balanced temperatures
- New high efficiency air screen technology
- Self contained system
- Hermetic unit
- Built-in condensate system included

OPTION

- Night Cover

IMPORTANT NOTE:

ALL REFRIGERATED CASES ARE DESIGNED TO OPERATE IN AN ENVIRONMENT OF 75 DEGREES AND 55% RELATIVE HUMIDITY.

PRODUCT MUST BE COOLED BEFORE BEING DISPLAYED WITHIN THE CASE.

DRAIN IS REQUIRED

SC-OD35E-33L-B-LED - MOBILE MERCHANDISER

TECHNICAL DATA

Model No.	SC	SC-OD35E-33L-B-LED
Length with (2) ends		33.75"
Length without ends		30.75"
Height with ends		60.00"
Height with casters		61.00"
Depth with ends		34.50"
Depth without ends		34.50"
Endless design (Dimensions are +/- 1/4")		YES
Operating temperature		38°F to 41°F
Compressor size HP		1/2
Defrost per day (24 hours)	Air Defrost	6
Voltage	SC	115
Amperage	SC	14.0
Cord and plug	SC	5-20P
Exterior color		Black
Interior color		Black
# of shelves		2 Shelves
Size of shelves		12.00", 14.00"

- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
- Cases are equipped with drains; check your local building codes for connection requirements.
- Specification subject to change without notice

DRAWINGS • SIDE VIEW • FRONT VIEW • PLAN VIEW

